

# Heavy Duty Industrial Fibreglass

## PRO SERIES FIBREGLASS EXTENSION LADDER



- Ladder lock assembly is standards conforming
- Hauling & delatching ropes at side position
- Tie off ropes at the top and bottom to secure ladder to pole
- Pole chain fitted as standard  
OR optional V rung & cable hook assembly with rubber pad
- Heavy duty fixed rubber feet as standard  
OR optional swivel feet  
OR optional ladder leveller assembly
- Load rating 150 kg
- Conforms to AS/NZ 1892.3.1996
- 5-year warranty\*

\* The warranty covers only faulty workmanship and materials when used under the definitions laid down in the AS/NZS 1892.5.2000

Model No	Height	Approx. Weight*
UFX13	2.7 - 4.0 m	19.0 kg
UFX17	3.4 - 5.2 m	23.0 kg
UFX21	4.0 - 6.4 m	26.0 kg
UFX25	4.6 - 7.6 m	30.0 kg
UFX29	5.2 - 8.8 m	33.5 kg

**Model: UFX17 - 3.4m - 5.2m**  
(fixed feet, cable hook + v rung and tie off ropes fitted)

\* The weight is for standard UFX only (fixed feet and pole chain fitted)

Safety and Electrical Resistance data is available from "Fibreglass Technical Manual" and it can be downloaded from [www.laddersolutions.com.au](http://www.laddersolutions.com.au)

## PRODUCT FEATURES



Hauling and ladder lock ropes at side position allow an unobstructed climbing path



Rung Catch Lock



Wide Body Fixed Feet

## ACCESSORIES



Automatic Ladder Leveller



Swivel Feet



Cable Hook and V-Bracket

Notice: The information contained in this brochure is subject to change without notice and should not be construed as a commitment by Ladder Solutions.

Ladder Solutions 2/12 Watsford Road Campbelltown NSW 2560 Ph: 02 4620 4011 Fax: 02 4620 4955  
Email: [sales@laddersolutions.com.au](mailto:sales@laddersolutions.com.au) Web: [www.laddersolutions.com.au](http://www.laddersolutions.com.au)